USED EQUIPMENT FOR SALE



MF 1839 small square baler.





'98 Sterling tractor, wet kit, 325,000 miles, '09 Muv-All dbl. drop 48', winch, alum. pull out, hyd. beavertail.



MF 4160V baler.



JD 7200, 12R, liquid

NH T7.260



SUNFLOWER. The 6631 Vertical Tillage Tool

VERTICAL TILLAGE TOOLS

Vertical tillage systems were created to address the varying needs of farmers. No-till or minimum till farmers found new crop varieties were more difficult to manage in terms of residue. For these farmers, a tool was needed to help breakdown residue without being as aggressive as a disc harrow. Other farmers had a diffe ent reason for wanting vertical tillage. These farmers had growing concerns over compaction layers caused by other types of tillage in non-ideal situations. What they needed was a tool that could help manage residue, better prepare soils for planting, all while reducing horizontal movement of the soil. Now moving into its second decade, Vertical tillage practices have had the time and opportunity to be observed and improved. The aim of vertical tillage practices is to manage residue, open soil for warming and drying, while minimizing horizontal movement of the soil - a situation that can cause compaction layers to form.

When used correctly, a vertical tillage tool should size residue for more rapid decomposition, pin and incorporate residue for enhanced erosion resistance, and lift soil vertically for partial sizing, soil warming and soil drying while avoiding compaction layers from the lateral movement of soil. To do the job right, a tool must have sharp blades and the ability to lift an adequate amount of soil vertically for incorporation.

12296 W. Brady (M-57) • Chesaning, Michigan 48616 www.cardbrothers.com

(989) <u>845-7</u>370



5035 Three-Section Field Cultivator

Heavy Construction, Outstanding Clearance and Superb Flotation

WORKING WIDTHS FROM 18'6" TO 36'6"

The Sunfl wer 5035 field cultivator's 3x4-inch rectangular tube frame provides the strength today's high-horsepower tractors require, and Sunfl wer's computer design features optimum shank placement for unmatched clearance. The model 5035 features single-point depth control with rephasing lift cylinders, all covered under our limited three-year warranty. Shanks are available in either spring-tension or S-tine design and offer up to 190 of point load for extra tough conditions. Walking tandems and 9.5L tires provide the fl tation farmers require of a field cultivator, and the selfleveling hitch maintains a level frame from front to rear, regardless of operating depth.



AGCO A smarter way to work.



- AC 7020
- White 8810
- (2) NH T7.260

COMBINES

- F-2
- S-97
- R-62

SPRAYERS

• 5100S 11R, Vertical fold

- Demco Conquest 1000, 60'
- NAV 1000 60' boom

• 7200, 12R, Liquid

• NAV 1100, 90' boom

- Killbros 475 cart
- Westfield 6x26
- Bush Hog BH6 cutter
- · Case IH 60 flail
- · Red Devil 84" dbl. snow blower
- Used 4160V baler
- Bush Hog 120-9 blade